



PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

- 1 HOUSING MATERIAL
- 2 CONTACT MATERIAL
- 3 PLATING
- 4 SHIELD
- 5 LED

ELECTRICAL:

- 1 VOLTAGE RATING :125 VAC RMS.
- 2 CURRENT RATING :15 AMP
- 3 CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4 INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC.
- 5 DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

- 1 DURRABILITY :750 CYCLES MIN.
- 2 PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1 STORAGE :-40°~+85°
- 2 OPERATION :0° TO 70°

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD												
CHECKED:	DATE:													
DRAWN:	DATE:	TITLE: RJ45-8P/8C 双层 2*1 弯插 带屏蔽 双带灯 无弹片												
SXA	2018-10-28	<table border="1"> <tr> <td>P/N</td> <td>R-RJ45R08P-C200</td> </tr> <tr> <td>UNIT</td> <td>mm</td> </tr> <tr> <td>SCALE</td> <td>Free</td> </tr> <tr> <td>FILE NO.</td> <td>Ckmtw-RJ45-0200</td> </tr> <tr> <td>REV.</td> <td>A</td> </tr> <tr> <td></td> <td>HY04</td> </tr> </table>	P/N	R-RJ45R08P-C200	UNIT	mm	SCALE	Free	FILE NO.	Ckmtw-RJ45-0200	REV.	A		HY04
P/N	R-RJ45R08P-C200													
UNIT	mm													
SCALE	Free													
FILE NO.	Ckmtw-RJ45-0200													
REV.	A													
	HY04													